


BP-361 .27cal Powder Actuated Tool



Technical Data

Dimensions: 16-1/8" x 2-1/8" x 6.1/2"
Weight: 5.0lb
Fastener Type: Flat & dome head pins or threaded studs
Fastener length: 1/2" - 1-7/8"
Load Type: .27cal. (6.8 x 11mm) strip loads
Power Level: Green/3, Yellow/4, Red/5



Applications and Advantages

- Commercial and residential construction
- Drywall track
- Conduit clips fastening
- Electrical fixtures
- Duct straps
- Wood to steel
- Wood to concrete
- Metal track
- Concrete forming
- Door frames
- Perimeter plates
- Furring Channel
- Brick Ties
- Automatic piston return and powder loads advance
- Variable level adjustment
- Reduces noise level

BP-361M Tool w/ Magazine



Technical Data

Dimensions: 16-1/4" x 2-1/8" x 8-3/4"
Weight: 5.4lb (with magazine)
Fastener Type: Flat and dome collated pins
Fastener length: 1/2" - 1-1/4"
Load Type: .27cal. (6.8 x 11mm) strip loads
Power Level: Green/3, Yellow/4, Red/5



Applications and Advantage

- Commercial and residential construction
- Drywall track
- Electrical fixtures
- Duct straps
- Wood to steel
- Wood to concrete
- Metal track
- Concrete forming
- Door forming
- Perimeter plates
- Furring channel
- Brickties
- Automatic piston return
- Automatic pins and powder loads advance
- Variable level adjustment
- Reduces noise level

BP-307S .22cal Powder Actuated Tool



The BP307S is a Low Velocity Powder Actuated, single shot, .22 caliber tool which can be used to install .300"-.315" head drive pins and 1/4"-20 threaded studs, up to 3" in total length. The BP307S is designed for maintenance, residential and commercial contractors.

Applications

- Conduit Clips to Concrete and Steel
- Drywall Track to Concrete and Steel
- Electrical Fixtures to Concrete and Steel
- Wood Furring Strips to Concrete
- Wood Perimeter Plates to Concrete
- Wood Framing Plates to Steel
- Hooks, Hangers and Cable ties to Concrete and Steel

Advantages

- Light Weight Durable Design
- Rubber Cushion Comfort Grip
- Automatic Cartridge Ejection
- Slim Profile Nose Piece 5/8" Diameter able to access tight areas
- Simple to Clean and Maintain – Service in the Field
- Replaceable Piston Buffer for Overdrive Protection
- Replaceable Piston and Piston Stop Guide
- Meets or Exceeds OSHA/ANSI A 10.3 Safety Standards
- Meets or Exceeds PATMI Standards
- Built in overdrive precision

.145" Diameter Shank Series Drive Pins:

PD Pins:

Model No.	Shank Length	Description	Package/Qty
PD13PK	1/2" Knurled	.300" head dia. pin w/plastic washer	100/1000/5000
PD16F10K	5/8" Knurled	.300" head dia. pin w/flute	100/1000/5000
PD19F10	3/4"		100/1000/5000
PD19F10BLB	3/4"	.300" head dia. track pin(Pinch point, black)	1000/5000
PD25F10	1"	.300" head dia. pin w/flute	100/1000/5000
PD32F10	1-1/4"		100/1000
PD38F10	1-1/2"		100/1000
PD42F10	1-5/8"		100/1000
PD44F10	1-3/4"		100/1000
PD47F10	1-7/8"		100/1000
PD51F10	51mm/ 2"		100/1000
PD57F10	2-1/4"		100/1000
PD63F10	2-1/2"		100/1000
PD76F10	3"		100/1000

Top Hats Pins:

Model No.	Shank Length	Description	Package/Qty
PDTH13F10K	1/2" knurled	.300" head dia. pin w/ top hat	100/1000/5000
PDTH16F10K	5/8" knurled		100/1000/5000
PDTH19F10	3/4"		100/1000/5000
PDTH25F10	1"		100/1000/5000
PDTH32F10	1- 1/4"		100/1000

Washer Pins:

Model No.	Shank Length	Description	Package/Qty	
PDW25-19F10	3/4"	.300" dia. head pin w/1" dia. metal washer	100/1000	
PDW25-25F10	1"		100/1000	
PDW25-32F10	1-1/4"		100/1000	
PDW25-38F10	1-1/2"		100/1000	
PDW25-51F10	2"		100/1000	
PDW25-63F10	2-1/2"		100/1000	
PDW25-73F10	2-7/8"		100/1000	
PDW25-76F10	3"		100/1000	
PDW22-19F10	3/4"		.300" dia. head pin w/7/8" dia. metal washer	100/1000
PDW22-25F10	1"			100/1000
PDW22-32F10	1-1/4"			100/1000
PDW19-19F10	3/4"	100/1000		
PDW19-25F10	1"	.300" dia. head pin w/3/4" dia. metal washer	100/1000	
PDW19-32F10	1-1/4"		100/1000	
PDW19-38F10	1-1/2"		100/1000	
PDW19-51F10	2"		100/1000	
PDW19-63F10	2-1/2"		100/1000	
PDW19-76F10	3"		100/1000	

Technical Data

Weight: 4.2 lbs
Length: 13.75"

Powder Loads

.22cal neck down single shot loads		
Brown	Green	Yellow

.157" Diameter Shank Series Drive Pins:

PD Pins:

Model No.	Shank Length	Description	Package/Qty
PD157-12PK	1/2"	.300" head dia. knurled pin w/ plastic washer	100/1000/5000
PD157-58F	5/8"	.300" head dia. pin w/ rubber flute	100/1000/5000
PD157-34F	3/4"		100/1000/5000
PD157-34FB	3/4", bulk		1000/5000
PD157-78F	7/8"		100/1000/5000
PD157-100F	1"		100/1000
PD157-114F	1-1/4"		100/1000
PD157-112F	1-1/2"		100/1000
PD157-158F	1-5/8"		100/1000
PD157-134F	1-3/4"		100/1000
PD157-178F	1-7/8"		100/1000
PD157-200F	2"		100/1000
PD157-214F	2-1/4"		100/1000
PD157-212F	2-1/2"		100/1000
PD157-300F	3"		100/1000

Top Hats Pins:

Model No.	Shank Length	Description	Package/Qty
PD157-78FTH	7/8"	.300" head dia. top hat pin	100/1000/5000

Washer Pins:

Model No.	Shank Length	Description	Package/Qty
PD157-114W	1-1/4"	.300" dia. head pin w/1" dia. metal washer	100/1000
PD157-112W	1-1/2"		100/1000
PD157-212W	2-1/2"		100/1000
PD157-300W	3"		100/1000

Actual Embedment Pins

Model No.	Shank Length	Description	Package/Qty
PD157-12PKAE	1/2"	.315" head slim groove shank AE pin w/ plastic washer	100/1000/5000
PD157-34AE	3/4"	.315" head dia. AE pin w/ rubber flute	100/1000/5000
PD157-100AE	1"		100/1000
PD157-114AE	1-1/4"		100/1000
PD157-112AE	1-1/2"		100/1000



BP-303A .27cal Powder Actuated Tool



Technical Data

Weight: 5 lbs Length: 14"
Pin Type: .300" / .315" / 8mm head pin,
 1/4" - 20 threaded stud
Pin Length: 1/2" to 3" total length
Load Type: .27cal. (6.8 x 11mm) 10 load
 strip, semi automatic load adjuster
Power Level: Green, Yellow, Red, Purple

Advantages:

- Adjustable power levels
- Shoots up to full 3" pins
- High strength durable piston
- Protective rubber front barrel sleeve for user protection

Applications:

- Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

BP-301C .27cal Powder Actuated Tool



Technical Data

Weight: 5 lbs Length: 13-5/8"
Pin Type: .300" / .315" / 8mm head pin,
 1/4" - 20 threaded stud
Pin Length: 1/2" to 2-1/2" total length
Load Type: .27cal. (6.8 x 11mm) 10 load
 strip, semi automatic load adjuster
Power Level: Green, Yellow, Red, Purple

Applications:

- Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

▲ BP-35 .25cal Powder Actuated Tool



Technical Data

Weight: 4.3 lbs **Length:** 11.42"
Pin Type: .300" / .315" / 8mm head pin,
 1/4" - 20 threaded stud
Pin Length: 1/2" to 1-1/2" total length
Load Type: .25cal. 10 load strip, semi auto-
 matic load adjuster
Power Level: Green, Yellow, Red

Applications:

- Track to floor
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial construction
- Reliable & compact for short
 pin applications

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

BP-307 .22cal Powder Actuated Tool



Technical Data

Weight: 4 lbs Length: 13.19"
Pin Type: .300" / .315" / 8mm head pin,
 1/4" - 20 threaded stud
Pin Length: 1/2" to 3" total length
Load Type: .22cal. neck down load
Power Level: Brown, Green, Yellow, Red

Applications:

- Track to floor
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential
 construction

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

▲ Available on Request