Pretied Ceiling Wire:

- ICC-ES ESR-1530 certified pins
- Meets or exceeds wire standards ASTM A641-92
- All wires are tied with the hospital wrap
- Tie requirement to ensure maximum holding power as dictated by building code
- Wire gauge:8 thru 12 gauge
- Length:2', 4', 6', 8', 10', 12', 14', 16', 18', 20' available
- Custom lengths also available
- Multiple wire termination options(see below)
- Wire can be purchased by:
  - a) Container for maximum savings
  - b) Bundles of 100pcs capped and wrapped securely
  - c) Master bundles of 20-100pc bundles
  - **d) Steel crates that are stackable**

Technical Data - 12 gauge wire		
Diameter	Tensile Range	Zinc Thick-ness
0.105"	75ksi max	≥25g/m2

Straight Cut Wires:

Coiled Wire:



Hospital Tied

Small bundle (Include 100pcs)

8 & 9 Gauge Tied

12 Gauge Double Tied

Master Bundle (Include 20 small bdls)

Steel Crate Quantity

Bundles / Steel crate	
Wire length 4"	160 bdls
Wire length 6"	140 bdls
Wire length 8"	120 bdls

Wire Attachment Options:

Electric EZ wire tie machine:

	Part No.	Description	Box	Case
	TWM1	Electric EZ wire tie machine/110V	1	1
	TWM2	Electric EZ wire tie machine/ 110V (Heavy duty, wire size up to 9 gauge)	1	1

Wire Attachment Options

	Product	Part No.	Description	Box	Case
※		EL300W	**3"** wood eye lag screw 'Plain'	100	1000
※		EL400W	**4"** wood eye lag screw 'Plain'	100	1000
※		EL500W	**5"** wood eye lag screw 'Plain'	100	1000
※		EL75SD	**2"** overall length, **~1/2"** thread length, **3/4"** from collar to self drill point. Used for **16** to **22** gauge sheet metal	100	1000
▲ ※	**5/16" BIG HOLE**	EL75BSD	**2"** overall length, **~1/2"** thread length, **3/4"** from collar to self drill point, **5/16" Eye.** Used for **16** to **22** gauge sheet metal	100	1000
※		EL150SP	**2-3/4"** overall length, **~1-1/2"** thread length	100	1000
※		EL200SD	**3-1/4"** overall length,**~1-3/4"** threaded length, **2"** from collar to drill point. Used for **16** to **22** gauge sheet metal	100	1000
		EL100DSD	**2-1/4"** overall length, **1"** from collar to drill point, **Deep Drilling** eye lag screw, **Blue Ruspert finish. Extra Wide tool tip** allows it to be used for up to **1/4"** thick structural steel	100	1000
		TWA14214	**1/4" x 2-1/4"** Tie wire wedge anchor	100	1000
		TWA14218	**1/4" x 2-1/8"** Tie wire anchor	100	1000
▲		TWSA14214	**1/4" x 2-1/4"** Tie wire split drive anchor	100	1000
		HBC25	Hammer-on beam clamp (**1/8" - 1/4"**)	100	1000
		HBC50	Hammer-on beam clamp (**5/16" -1/2"**)	100	1000
		PCZ25	Z-Purlin clip (**1/8" -1/4"**)	100	1000
		PC25	C-Purlin clip (**1/8" - 1/4"**)	100	1000
		AC90	**90** degree angle clip	100	1000
		AB90	**12** gauge heavy duty clip, **90** degree	100	1000
		SP45	**12** gauge heavy duty clip, **45** degree	100	1000

▲ **Available on Request**

※ **Bright Zinc Plating Available on Request**