


Pretied Ceiling Wire:

- ° ICC-ES ESR-1530 certified pins
- Meets or exceeds wire standards ASTM A641-92
- All wires are tied with the hospital wrap
- Tie requirement to ensure maximum holding power as dictated by building code
- ° Wire gauge:8 thru 12 gauge
- ° Length:2', 4', 6', 8', 10', 12', 14', 16', 18', 20' available
- ° Custom lengths also available
- Multiple wire termination options(see below)
- Wire can be purchased by:
 - a) Container for maximum savings
 - b) Bundles of 100pcs capped and wrapped securely
 - c) Master bundles of 20-100pc bundles
 - d) Steel crates that are stackable



Straight Cut Wires:





Steel Crate Quantity


Bundles / Steel crate			
Wire length 4"	160 bdls		
Wire length 6"	140 bdls		
Wire length 8"	120 bdls		





Small bundle (Include 100pcs)









Electric EZ wire tie machine:

	Part No.	Description	Вох	Case
	TWM1A	Electric EZ wire tie machine/110V	1	1
	TWM3	Electric EZ wire tie machine/ 230V (for 8 and 9 gauge wire)	1	1



Wire Attachment Options

	Product	Part No.	Description	Вох	Case
	94444444444	EL300W	3" wood eye lag wood screw/ plain	100	1000
		EL300WB	3" wood eye lag wood screw/ plain/ Bulk	-	1000
		EL300WZ	3" wood eye lag wood screw/ white zinc	100	1000
		EL300WZB	3" wood eye lag wood screw/ white zinc/ Bulk	-	1000
		EL400W	4" wood eye lag wood screw/ plain	100	1000
*		EL400WB	4" wood eye lag wood screw/ plain/ Bulk	-	1000
		EL500W	5" wood eye lag wood screw/ plain	100	1000
		EL500WB	5" wood eye lag wood screw/ plain/ Bulk	-	1000
	In the second se	EL75SD	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1000
		EL75SDB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	1000
		EL75SDZ	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1000
		EL75SDZB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	1000
*	5/16" BIG HOLE	EL75BSD	2" overall lgth, ~1/2" thread lgth, 3/4" from collar to self drill point, 5/16" Eye. Used for 16 to 22 gauge sheet metal.	100	1000
*		EL150SP	2-3/4" overall lgth, ~ 1-1/2" thread lgth. Sharp point. Used for 20 to 22 gauge metal decking and also in wood applications.	100	1000
*		EL200SD	3-1/4" overall lgth,~1-3/4" threaded lgth, 2" from collar to drill point. Used for 16 to 22 gauge sheet metal.	100	1000
-		EL100DSD	2-1/4" overall lgth, 1" from collar to drill point, Deep Drilling eye lag screw, Blue Ruspert finish. Extra Wide tool tip enables it to be used for up to 1/4" thick structural steel.	100	1000
	- mununum	EL14114	2-1/2" overall length, Concrete Eye Lag Screw, Blue Ruspert finish. High-low thread, thread lgth 1-1/4".	100	1000
		TWA14214	1/4" x 2-1/4" Tie wire wedge anchor	100	1000
	Control along pages	TWA14218	1/4" x 2-1/8" Tie wire anchor	100	1000
A		TWSA14214	1/4" x 2-1/4" Tie wire split drive anchor	100	1000
		HBC25	Hammer-on beam clamp (1/8" - 1/4")	100	1000
	0 '	HBC50	Hammer-on beam clamp (5/16" -1/2")	100	1000
		PCZ25	Z-Purlin clip (1/8" -1/4")	100	1000
		PC25	C-Purlin clip (1/8" - 1/4")	100	1000
	1	AC90	90 degree angle clip	100	1000
		AB90	12 gauge heavy duty clip, 90 degree	100	1000
		SP45	12 gauge heavy duty clip, 45 degree	100	1000

- ▲ Available on Request
- Bright Zinc Plating Available on Request