

2024 1ST EDITION(1)

America's Powder Actuated Fasteners Specialist

EXCLUSIVE TO BLUE POINT FASTENERS


Noise-Canceling Fastening Tool



Specially designed for all day fastening in occupied spaces such as Hospitals, Schools, Offices etc.



Engineered by BLUEPOINT TECHNOLOGY™





WHO IS BLUE POINT FASTENERS?

BLUE POINT FASTENERS is an international manufacturer of high quality and innovative construction fastening solutions, hanging systems and specialty equipment. **A value engineering approach** to our innovative products allows BLUE POINT FASTENERS to be competitive while retaining high quality, contractors are looking for.

Holding numerous U.S. and International Patents, BLUE POINT FASTENERS continues to produce products that will innovate how engineers, contractors and owners can save time and money on current and future projects.

WHAT MAKES BLUE POINT DIFFERENT?

LOOK BELOW.....

- * PREMIER PRETTIED HANGING WIRE MANUFACTURER IN THE U.S. MARKET
- NO LEAD DIRECT FASTENING
- ° QUIET DIRECT FASTENING
- LOW LEAD POWDER LOADS
- POST TENSION AND HIGH-PRESSURE SLAB DIRECT FASTENING SOLUTIONS
- STEEL APPLICATIONS BEST DRIVE PINS FOR STEEL
- MAGNESIUM ALLOY ACOUSTIC POLES / LARGEST SELECTION OF ADAPTERS
- CUSTOM ACOUSTIC HANGING SOLUTIONS
- LOW VOLTAGE AND DATACOM HANGING LARGE SELECTION
- * HEAVY DUTY DUMP CARTS HIGHEST LOAD CAPACITY IN THE MARKET

Specialties:

- Product Developing and Manufacturing
- Powder Actuated, Gas and Nitrocellulose Fastening Solutions
- Acoustical Hanging Solutions
- Electrical and Data Comm Hanging Solutions
- Concrete/Steel Fastening and Drilling Solutions
- Jobsite Equipment and Tools

















Table Of Contents

And the second s	POWDER ACTUATED TOOLS (PAT) 2-4
	POWDER LOADS
999999999	DRIVE PINS
7	GAS TOOLS/ GAS PINS/ FUEL CELL
	NITRO NINJA TOOL, PINS & CLIPS 12-13
	BP-27C POWDER ACTUATED TOOL
	NINJA ACOUSTIC POLE ADAPTER SYSTEMS 15-16
	RIVETS/ RIVETERS
7 3	INSULATION TOOL/ PINS/ WASHERS
	WIRE HANGING SYSTEMS
	TOGGLE BOLTS/ SCREWS
	HOOKS/ HANGERS
	J HOOKS 24
	ANCHORS/ CONCRETE SCREWS
122222	DRILL BITS 28-29
	DUMP CARTS 30
	SERVICE CARTS
	AIR & WATER HOSES

Bluepoint Fasteners www.bpfasteners.com 877-779-2583 **1**

POWDER ACTUATED FASTENING TOOLS (PAT)



BP-361

.27cal Automatic Powder Actuated Tool



Technical Data

Dimensions: 16-1/8" x 2-1/8" x 6.1/2"

Weight: 5.0lb

Fastener Type: Flat & dome head pins or threaded studs

Fastener length: 1/2" - 1-7/8"

Load Type: .27cal. (6.8 x 11mm) strip loads



Applications and Advantages

- ° Commercial and residential construction
- Drywall track
- ° Conduit clips fastening
- ° Electrical fixtures
- Duct straps
- Wood to steel
- Wood to concrete
- Metal track
- Concrete forming
- ° Door frames
- Perimeter plates
- Furring Channel
- Brick Ties
- Automatic piston return and powder loads advance
- Variable level adjustment
- ° Reduces noise level

BP-361M

.27cal Automatic Tool w/ Magazine



Technical Data

Dimensions: 16-1/4" x 2-1/8" x 8-3/4"
Weight: 5.4lb (with magazine)
Fastener Type: Flat and dome collated pins

Fastener length: 1/2" - 1-1/4"

Load Type: .27cal. (6.8 x 11mm) strip loads



Applications and Advantage

- ° Commercial and residential construction
- Drywall track
- Electrical fixtures
- Duct straps
- Wood to steel
- ° Wood to concrete
- Metal track
- Concrete forming
- ° Door forming
- Perimeter plates
- Furring channel
- Brickties
- Automatic piston return
- Automatic pins and powder loads advance
- Variable level adjustment
- ° Reduces noise level





BP-302A

.27cal Noise Canceling Semi-Automatic Powder Actuated Tool w/ Power Adjuster

* Specially designed for all day fastening in occupied spaces such as Hospitals, Schools, Offices etc.





Technical Data

Weight: 5.5 lbs Length: 13-3/4" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 2-1/2" total length Load Type: .27cal. 10 load strip.

Brown/2 Green/3 Yellow/4 Red/5 Purple/6

Commercial & residential construction

Concrete forming

Wood to concrete/steel

Conduit clip to concrete

Electrical fixture to concrete/ steel

Applications:

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

Advantages:

- · Adjustable power levels
- Very low noise
- Shoots up to full 2-1/2" pins
- · High strength durable piston

BP-301C

.27cal Semi-Automatic Powder Actuated Tool



Technical Data

Weight: 5 lbs Length: 13-5/8" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 2-1/2" total length Load Type: .27cal. 10 load strip.

Brown/2 Green/3 Yellow/4 Red/5 Purple/6

Applications:

- Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Advantages:

- Most popular and reliable tool in the market
- Most parts inter-changeable with other brand tools

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

BP-303A

.27cal Semi-Automatic Powder Actuated Tool w/ Power Adjuster



Technical Data

Weight: 5 lbs Length: 14" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .27cal. 10 load strip.

Brown/2 Green/3 Yellow/4 Red/5 Purple/6

Applications:

- Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Advantages:

- Adjustable power levels
- Shoots up to full 3" pins
- High strength durable piston
- Protective rubber front barrel sleeve for user protection

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

POWDER ACTUATED FASTENING TOOLS (PAT)



BP-307S

.22cal Single Shot Powder Actuated Tool



Technical Data

Weight: 4.2 lbs Length: 13-3/4" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .22cal. neck down single shot

Brown/2 Green/3 Yellow/4 Red/5

Advantages:

- Light Weight Durable Design w/ Rubber Cushion Grip
- Automatic Cartridge Ejection
- Replaceable Piston Buffer for Overdrive Protection
- Replaceable Piston and Piston Stop Guide
- Meets or Exceeds OSHA/ ANSI A 10.3/ PATMI Safety Standards

Applications:

- Conduit clip to concrete/ Steel
- Drywall Track to Concete/ Steel
- Electrical fixture to Concrete/ Steel
- Wood Furring Strips/ Perimeter Plates to Concrete
- Wood Framing Plates to Steel
- Hooks, Hangers and Cable ties to Concrete/ Steel

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

BP-307 .22cal Powder Actuated Tool



Technical Data

Weight: 4 lbs Length: 13.19" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .22cal. neck down load.

Brown/2 Green/3

Yellow/4 Red/5

Applications:

- Track to floor
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

BP-H01

.22cal Single Shot Hammer Activated Tool







Technical Data

Weight: 2.2 lbs Length: 13-9/16" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .22cal. neck down single shot

Brown/2 Green/3 Yellow/4 Red/5

Advantages:

- Light Weight Durable Design w/ Rubber Cushion Grip
- Automatic Cartridge Ejection
- Replaceable Piston Buffer for Overdrive Protection
- Replaceable Piston and Piston Stop Guide
- Meets or Exceeds OSHA/ ANSI A 10.3/ PATMI Safety Standards

Applications:

- Conduit clip to concrete/ Steel
- Drywall Track to Concete/ Steel
- Electrical fixture to Concrete/ Steel
- Wood Furring Strips/ Perimeter Plates to Concrete
- Wood Framing Plates to Steel
- Hooks, Hangers and Cable ties to Concrete/ Steel

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

Bluepoint Fasteners www.bpfasteners.com 877-779-2583





*Enhanced strips are good for heavy duty and full automatic fastening tools
















Model No.	Package/Qty	Size	Description	Color	Power	Power Level
27ES11L6	100 10000	6.8 x 11	.27cal Enhanced strip loads	Purple	Strongest	6
27ES11L5	100 10000	(mm)		Red	Strong	5
27LS11L5	100 10000		3.8 v 11	Red	Strong	5
27LS11L4	100 10000	6.8 x 11		Yellow	Medium	4
27LS11L3	100	(mm)	.27cal long strip loads	Green	Low	3
27LS11L2	100 10000			Brown	Lowest	2
25SS10L5	100			Red	Strong	5
25SS10L4	100	6.3 x 10		Yellow	Medium	4
25SS10L3	100	(mm)	.25cal strip loads	Green	Low	3
25SS10L2	10000			Brown	Lowest	2
25MD10L5	10000			Red	Strong	5
25MD10L4	10000 10000 10000	6.3 x 10		Yellow	Medium	4
25MD10L3	10000 10000 10000	(mm)		Green	Low	3
25MD10L2	10000 10000 10000			Brown	Lowest	2
22SGNDL5	10000			Red	Strongest	5
22SGNDL4	10000		.22cal neck down single shot loads	Yellow	Strong	4
22SGNDL3	100 100 10000	5.6 x 16		Green	Medium	3
22SGNDL2	10000	(mm)		Brown	Low	2
22SGNDL1	100			Gray	Lowest	1
22L4B	100		.22cal neck down single shot loads, brass case	Yellow	Strong	4
22SGSWL6	100 10000		oner issues, since succ	Purple	Strong	6
22SGSWL5	100	5.6 x 15	.22cal straight wall single shot	Red	Medium	5
22SGSWL4	10000	(mm)	loads	Yellow	Low	4
22SGSWL3	100 100 10000			Green	Lowest	3
22SL6B	100 100 10000			Purple	Strong	6
22SL5B	10000	5.6 x 15	.22cal straight wall single shot	Red	Medium	5
22SL4B	10000	(mm)	loads, Brass casing for Ninja tool	Yellow	Low	4
22SL3B	10000			Green	Lowest	3
27SGL3LB	10000			Purple	Strong	6
27SGL4LB		6.8 x 18	.27cal (6.8*18) single shot	Red	Medium	5
27SGL5LB		(mm)	long loads, brass case	Yellow	Low	4
27SGL6LB				Green	Lowest	3



Actual Embedment Drive Pins







Advantages

- ° The Blue Point .157" diameter shank Actual Embedment (AE) pin is sized to provide actual embedment depths in track or clips up to 14 gauge (2mm).
- Assured to meet the required embedment depths into concrete or steel without compensating for the track or clip thickness.
- The pin heads are stamped for easy identification before and after installation.
- Choose the correct pins confidently For example, using the 1" AE pin, the actual embedment depth into the concrete is 1". There is no longer a need to use a 1-1/4" pin to assure a 1" embedment.
- Nominal .315" head diameter, thick heavy duty head provide true guidance for better drivability.
- Available in single shot and strip pin applications

Single Drive Pins

	Item No.	Shank Length	Description	Package/ Qty
A	PD157-12PKAE	1/2"	.315" head, .157" dia. shank knurled AE pin w/ plastic washer	100/1000/5000
	PD157-12FKAE	1/2"	.315" head, .157" dia. shank knurled AE pin w/ rubber flute	100/1000/5000
	PD157-34FAE	3/4"		100/1000/5000
A	PD157-100FAE	1"	.315" head dia., .157" dia. shank	100/1000
A	PD157-114FAE	1-1/4"	E pin w/ rubber flute	100/1000
A	PD157-112FAE	1-1/2"		100/1000

Collated Drive Pins

	Item No.	Shank Length	Description	Package/ Qty
A	PDC157-12KAE	1/2"	.315" head, .157" dia. shank knurled AE pin w/ plastic strip	100/1000/5000
	PDC157-34AE	3/4"		100/1000/5000
	PDC157-100AE	1"	.315" head dia., .157" dia. shank AE pin w/ plastic strip	100/1000
A	PDC157-114AE	1-1/4"		100/1000
	PDC157-112AE	1-1/2"		100/1000

*.315" Dia. Head, .157" dia. Shank Premium Steel Pin

Item No.	Shank Length	Description	Box	Case	Master Box
PP58SG	5/8"	Slim groove shank with plastic washer	100	1000	5000

*.300" Dia. Head, .181"/.150" Step Shank dia. Premium Pin

Item No.	Shank Length	Description	Box	Case	Master Box
PP181S-178F	1-7/8"	.300" dia. head, .181"150" step shank premium pin.	100	1000	5000

Available on Request





.300" Dia. Head, .157" Dia. Shank Drive Pins

Plain Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
PD157-12PK	1/2"	Knurled Shank with plastic washer	100	1000	5000
PD157-12FK	1/2"	Knurled Shank with rubber flute	100	1000	5000
PD157-58F	5/8"	Smooth shank with rubber flute	100	1000	5000
PD157-34F	3/4"	Smooth shank with rubber liute	100	1000	5000
PD157-34FB	3/4"	Smooth shank with rubber flute/bulk	-	1000	5000
PD157-78F	7/8"		100	1000	5000
PD157-100F	1"	1	100	-	1000
PD157-114F	1-1/4"	1	100	-	1000
PD157-112F	1-1/2"]	100	-	1000
PD157-158F	1-5/8"]	100	-	1000
PD157-134F	1-3/4"	Smooth shank with rubber flute	100	-	1000
PD157-178F	1-7/8"		100	-	1000
PD157-200F	2"		100	-	1000
PD157-214F	2-1/4"		100	-	1000
PD157-212F	2-1/2"]	100	-	1000
PD157-300F	3"	1	100	-	1000





Collated Drive Pins:

Item No.	Shank Length	Description	Box	Case			
PDC157-12K	1/2"	Knowled about with plactic atria	100	1000			
PDC157-34K	3/4"	Knurled shank with plastic strip	100	1000			
PDC157-34	3/4"		100	1000			
PDC157-78	7/8"		100	1000			
PDC157-100	1"		100	1000			
PDC157-114	1-1/4"	Smooth shank with plastic strip	100	1000			
PDC157-112	1-1/2"	Smooth shank with plastic strip	100	1000			
PDC157-200	2"		100	1000			
PDC157-212	2-1/2"		100	1000			
PDC157-278	2-7/8"		100	1000			



Washer Pins:

Item No.	Shank Length	Description	Box	Case
PD157-114W	1-1/4"	With 1" dia. metal round washer	100	1000
PD157-112W	1-1/2"		100	1000
PD157-212W	2-1/2"		100	1000
PD157-300W	3"		100	1000



Heavy Mechanical Galvanized Washer Pins:

Item No.	Shank Length	Description	Box	Case
PD157-200WMG	2"	.300" dia. head, .157" dia. shank	100	1000
PD157-212WMG	2-1/2"	drive pins w/1" dia. metal round	100	1000
PD157-278WMG	2-7/8"	washer - Heavy mechanical galvanized for	100	1000
PD157-300WMG	3"	pressure-treated wood	100	1000



Angle Clip Pins:

Item No.	Shank Length	Description	Box	Case
PD157-100C90	1"		100	1000
PD157-100C90B		With 00° and alin	-	1000
PD157-114C90	1-1/4"	With 90° angle clip	100	1000
PD157-114C90B			-	1000
PD157-78THC90	7/8"	With Top hat and 90° angle clip	100	1000
PD157-78THC90B	776		-	1000
PD157-78HNC	7/8"		100	1000
PD157-100HNC	1"	With Top hat and Ninja Clip	100	1000
PD157-114HNC	1-1/4"		100	1000





.300" Dia. Head, .145" Dia. Shank Drive Pins

Plain Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
PD13F10K	1/2"	Knurled shank pin with flute	100	1000	5000
PD13PK	1/2"	Knurled shank pin with plastic washer	100	1000	5000
PD16F10K	5/8"	Knurled shank pin with flute	100	1000	5000
PD19F10	3/4"	Smooth shank pin with flute	100	1000	5000
PD19PFBL	3/4"	Pinch point track pin (black)	-	1000	5000
PD19FBLB	3/4"	Track pin (black) with flute/ bulk	-	1000	5000
PD19PFBLB	3/4"	Pinch point track pin (black)/ bulk	-	1000	5000
PD22F10	7/8"		100	1000	5000
PD25F10	1"		100	1000	5000
PD32F10	1-1/4"		100	-	1000
PD38F10	1-1/2"		100	-	1000
PD44F10	1-3/4"	Smooth about nin with flute	100	-	1000
PD47F10	1-7/8"	Smooth shank pin with flute	100	-	1000
PD51F10	2"		100	-	1000
PD57F10	2-1/4"		100	-	1000
PD63F10	2-1/2"		100	-	1000
PD76F10	3"		100	-	1000



Heavy Mechanical Galvanized Drive Pins:

Item No.	Shank Length	Description	Box	Case
PD38FMG	1-1/2"	.300" dia. head, .145" dia. shank, drive	100	1000
PD51FMG	2"	pin, Heavy mechanical galvanized	100	1000
PD63FMG	2-1/2"		100	1000
PD76FMG	3"	for pressure-treated wood	100	1000



▲ Collated Drive Pins:

Shank Length	Description	Box	Case
1/2"	Knurled should him with pleatic etrip	100	1000
3/4"	Knuned snank pin with plastic strip	100	1000
3/4"	Track pin (black) with plastic strip/bulk	-	1000
3/4"		100	1000
7/8"		100	1000
1"		100	1000
1-1/4"		100	1000
1-1/2"	Smooth shank pin with plastic strip	100	1000
2"		100	1000
2-1/2"		100	1000
2-7/8"		100	1000
	1/2" 3/4" 3/4" 3/4" 7/8" 1" 1-1/4" 2" 2-1/2"	1/2" 3/4" Knurled shank pin with plastic strip 3/4" Track pin (black) with plastic strip/bulk 3/4" 7/8" 1" 1-1/4" 1-1/2" 2" 2-1/2" Knurled shank pin with plastic strip Smooth shank pin with plastic strip	1/2"



Washer Pins:

Item No.	Shank Length	Description	Box	Case
PDW19-19F10	3/4"	Pin with 3/4" diameter metal round washer	100	1000
PDW19-25F10	1"	Pin with 3/4 diameter metal found washer	100	1000
PDW25-19F10	3/4"		100	1000
PDW25-25F10	1"		100	1000
PDW25-32F10	1-1/4"		100	1000
PDW25-38F10	1-1/2"	Pin with 1" diameter metal round washer	100	1000
PDW25-51F10	2"		100	1000
PDW25-63F10	2-1/2"		100	1000
PDW25-76F10	3"		100	1000
PDW25-25F10C	1"	Contractor pin with 1" diameter metal round	100	1000
PDW25-32F10C	1-1/4"	washer	100	1000
PDSW28-76F10	3"	Pin with 28mm dia. square metal washer	100	1000



Angle Clip Pins:

•				
Item No.	Shank Length	Description	Box	Case
PDAC120-25F10	4"	Pin with 125° angle clip	100	1000
PDAC120-25F10B] '	Pin with 125° angle clip/Bulk	-	1000
PDAC120-32F10	1-1/4"	Pin with 125° angle clip	100	1000
PDAC120-32F10B	1-1/4	Pin with 125° angle clip/Bulk	-	1000
PDAC90-25F10	1"	Pin with 90° angle clip	100	1000
PDAC90-25F10B	'	Pin with 90° angle clip/Bulk	-	1000
PDAC90-32F10	1-1/4"	Pin with 90° angle clip	100	1000
PDAC90-32F10B	1-1/4	Pin with 90° angle clip/Bulk	-	1000
PDAC90-38F10	1-1/2"	Pin with 90° angle clip	100	1000





▲ Available on Request

8 Bluepoint Fasteners www.bpfasteners.com 877-779-2583



8mm Head, .157" Spiral Knurled Shank Drive Pins

Spiral Knurled Collated Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
DNC157-34SK	3/4"		100	1000	5000
DNC157-78SK	7/8"		100	1000	-
DNC157-100SK	1"	Knurled shank pin with plastic washer	100	1000	-
DNC157-114SK	1-1/4"		100	1000	-
DNC157-112K	1-1/2"		100	1000	-
DNC157-158SK	1-5/8"		100	1000	-
DNC157-200SK	2"		100	1000	-

- Designed for fasteneing in both cocrete or steel.
- Compatible with Blue Point BP-361 tool and most other brand magazine tools.
- Also available as single pins (Box: 100; Case: 1000)



Plain Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
DN13P8K	1/2"		100	1000	5000
DN16P8K	5/8"	Kurled shank with plastic washer	100	1000	5000
DN19P8K	3/4"		100	1000	5000
DN22P8	7/8"		100	1000	5000
DN27P8	1"		100	1000	-
DN32P8	1-1/4"		100	1000	-
DN37P8	1-1/2"	With plastic washer	100	1000	5000
DN52P8	2"		100	1000	5000
DN62P8	2-1/2"		100	1000	5000
DN72P8	2-7/8"		100	1000	5000



Top Hat Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
DNTH16P8K	5/8"	Knurled shank with plastic washer	100	1000	5000
DNTH22P8	7/8"	\A/ith plactic weeker	100	1000	5000
DNTH25P8	1"	With plastic washer	100	1000	-



Collated Drive Pins:

Item No.	Shank Length	Description	Box	Case
DNC13K	1/2"	Knurled shank with plastic strip	100	1000
DNC19K	3/4"	Khuneu sharik with plastic strip	100	1000
DNC19	3/4"		100	1000
DNC22	7/8"		100	1000
DNC27	1"		100	1000
DNC32	1-1/4"	Currently about with wheeting atria	100	1000
DNC37	1-1/2"	Smooth shank with plastic strip	100	1000
DNC52	2"	,	100	1000
DNC62	2-1/2"		100	1000
DNC72	2-7/8"		100	1000



Angle Clip Pins:

Item No.	Shank Length	Description	Box	Case
DNACTH90-27P8	1"	With Top hat and 90° angle clip	100	1000
DNACTH90-32P8	1-1/4"	With Top hat and 90° angle clip	100	1000



.300" Dia. Head, .145" Dia. pin w/ Conduit Clip

Conduit Clip Pins:

Item No.	Shank Length	Description	Box	Case
CC25-P25	1"	With 1/4" conduit clip	100	1000
CC38-P25	1"	With 3/8" conduit clip	100	1000
CC50-P25	1"	Mith 1/0" acaduit alia	100	1000
CC50-P32	1-1/4"	With 1/2" conduit clip	100	1000
CC75-P25	1"	With 3/4" conduit clip	50	500
CC75-P32	1-1/4"	With 5/4 Conduit Clip	50	500
CC100-P25	1"	With 1" conduit clip	50	500
CC100-P32	1-1/4"	With a conduit clip	50	500





Threaded Studs

1/4"-20 threaded studs:

Item No.	Thread Length	Shank Length	Description	Box	Case
M1/4-19-13D12K	3/4"	1/2"		100	1000
M1/4-19-25D12		1"	With 1/2" plastic and metal washer	100	1000
M1/4-19-32D12		1-1/4"		100	1000
M1/4PH-13-13F10	1/2"	1/2"		100	1000
M1/4PH-13-25F10		1"		100	1000
M1/4PH-19-13F10K		1/2"	With .300" thread cap and rubber flute	100	1000
M1/4PH-19-25F10		1"		100	1000
M1/4PH-19-32F10		1-1/4"		100	1000





3/8"-16 Threaded Studs:

Item No.	Thread Length	Shank Length	Description	Box	Case
M3/8-32-16F10K	1-1/4"	5/8"k	With rubber flute	100	1000
M3/8-32-19F10K		3/4"k		100	1000
M3/8-32-25F10		1"	Will lubber lidle	100	1000
M3/8-32-32F10	1-1/4"		100	1000	



Other Drive Pins

5.7mm Dia. Head, .145" Dia. Shank Drive Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
NK16W12K	5/8"		100	1000	5000
NK19W12K	3/4"		100	1000	5000
NK22W12K	7/8"		100	1000	5000
NK27W12	1"	With 1/2" metal washer	100	1000	5000
NK32W12	1-1/4"		100	-	1000
NK37W12	1-1/2"		100	-	1000
NK42W12	1-5/8"		100	-	1000
NK52W12	2"		100	-	1000
NK57W12	2-1/4"		100	-	1000
NK72W12	2-7/8"		100	-	1000



Timber Clip Pin:

Item No.	Shank Length	Description	Box	Case
TBC250	2-1/2"	.312" Diameter Head, .172" diameter shank timber pin with 125° angle clip	100	1000



ANTFAST™ Drive Pins

Drive Pins:

Item No.	Shank Length	Description	Box	Case	Master Box				
PD13FKE	1/2"	.300 head, .145" dia. shank, contractor knurled pin w/rubber flute	100	1000	5000				
PD25F10E	1"		100	1000	5000				
PD32F10E	1-1/4"		100	-	5000				
PD38F10E	1-1/2"	.300 head, .145" dia. shank, contractor	100	-	5000				
PD51F10E	2"	pin w/flute	100	-	5000				
PD63F10E	2-1/2"		100	-	5000				
PD76F10E	3"		100	-	5000				





Washer Pins:

Item No.	Shank Length	Description	Box	Case
PDW25-25F10E	1"		100	1000
PDW25-32F10E	1-1/4"		100	1000
PDW25-38F10E	1-1/2"	.300 head, .145" dia. shank, contractor pin w/1" washer	100	1000
PDW25-51F10E	2"		100	1000
PDW25-63F10E	2-1/2"		100	1000
PDW25-76F10E	3"		100	1000



Angle Clip Pins:

Item No.	Shank Length	Description	Box	Case
PDAC120-25F10E	1"	.300 head, .145" dia. shank, contractor	100	1000
PDAC120-32F10E	1-1/4"	pin with 125° angle clip	100	1000
PD32CXE	1-1/4"	.300 head, .145" dia. shank, contractor pin w/ XP clip	100	1000





	Item No.	Description
	GT-100L	Gas fastening tool
BUEPOINT		ol takes up to 1-1/2" pins and the fuel cell compatible Ramset®, Simpson® . Easy to operate and no special Licensing is required.

Features

- Fast: 40-pin magazine and 1,200-shot fuel cell for reduced loading time
- Easy to use: Automatic piston reset
- · Easy open jam release door
- Portable: No hoses, cords, or external energy source required
- Convenient: Simple 2-step pin loading and open-blade guide-jam release
- Easy-load fuel compartment
- No possibility of firing with no pins when tool is down to last 2 pins in the pin magazine a "lock off" occurs
- Ladder hook

Applications


- Acoustical
- Drywall
- Electrical
- Data Com
- General Purpose
- Framing
- Mechanical
- Residential

Tool Specs

Tool dimensions: Length: 15", Width: 4.2"

- Height: 14"
- Weight: 7.4 lbs
- Magazine capacity: 30
- Average number of fastens per fuel cell: 1,200
- Average number of fastens per battery charge: 3,300
- Average battery charge time: 2 hours
- Fastener type: Length 1/2" to 1 1/2", Diameter .100" to .109"

		Item No.	Description	Box	Case
		PT13G	.106" Shank Dia., 1/2" shank length collated pin w/ fuel cell	1000	5000
		PT19G	.106" Shank Dia., 3/4" shank length collated pin w/ fuel cell	1000	5000
		PT25G	.106" Shank Dia., 1" shank length collated pin w/ fuel cell	1000	5000
	4	PT38G	.106" Shank Dia., 1-1/2" shank length collated pin w/ fuel cell	1000	5000
	3	PT12SG	.102"/.120" step shank, 1/2" shank length collated pin w/ fuel cell	1000	5000
۱ ۱	1	PT34SG	.102"/.120" step shank, 3/4" shank length collated pin w/ fuel cell	1000	5000
	3	PT100SG	.102"/.120" step shank, 1" shank length collated pin w/ fuel cell	1000	5000
	13	PT114SG	.102"/.120" step shank, 1-1/4" shank length collated pin w/ fuel cell	1000	5000
		All colla	ted pins also fits most Powers®, Ramset®, Simpson® and other		
			gas tools. Box includes 1000 pins + 1 fuel cell.		



Accessories	Item No.	Description	Quantity
(Dawerount,	FC6(2)	Blister packed 6" fuel cell	2pcs/ blister package, 12pcs/ box

▲ Available on Request





Technical Data:

Fastener Type: Nitro Ninja pins;

Fastener Length: 3/4" - 1-7/8"

Pretied Wires with Nitro Ninja pins

Weight: 3.25 lbs

Length: 16-3/4"

Nitro Ninja Tool







"Excellent holding values in hard concrete"

Special Features

- No Lead
- Low Noise
- Low Failure Rate
- No Piston
- Low Kickback
- Low Maintenance
- Narrow Profile
- Overhead (Ceilings) Floor Wall fastening
- High Pressure Concrete Post Tension Slabs
- Pre-tied Wire Straight Pins Angle Clips Threaded Rod Clips - Conduit Clamps - Zip Tie Clips



NT2001



NT2001 with Handle

for Wall & Floor Applications



NT2001 Kit

Item No.	Description	Quantity
NT2001	NT2001 Tool	1
NT2001-17	Handle	1
NT2001-18	Extension Pole	1



Item No.	Description
N ID4	Fastening tool bag w/ compartments & shoulder strap 16.5"x8.0"x9.0"







.300" Dia. Head, .157" Dia. Shank Nitro Ninja Drive Pins:

Plain Pins:

Item No.	Description	Jar/ Box	Case
PD157-12NB/ PD157-12NR	.157 dia. shank, 1/2" shank lgth nitro pin (black/ red)	500	-
PD157-34NB/ PD157-34NR	.157 dia. shank, 3/4" shank lgth nitro pin (black/ red)	500	5000
PD157-100NB/ PD157-100NR	.157 dia. shank, 1" shank lgth nitro pin (black/ red)	500	5000
PD157-114NB/ PD157-114NR	.157 dia. shank, 1-1/4" shank lgth nitro pin (black/ red)	500	5000
PD157-112NB/ PD157-112NR	.157 dia. shank, 1-1/2" shank lgth nitro pin (black/ red)	500	5000





Angle Clip Pins:

Item No.	Description	Jar	Case
PD157-78HNCNB/ PD157-78HNCNR	.157 dia. shank, 7/8" shank lgth top hat nitro pin (black/ red) w/NJ clip	100	1000
PD157-100HNCNB/ PD157-100HNCNR	.157 dia. shank, 1" shank lgth top hat nitro pin (black/ red) w/NJ clip	100	1000
PD157-114HNCNB/ PD157-114HNCNR	.157 dia. shank, 1-1/4" shank lgth top hat nitro pin (black/ red) w/NJ clip	100	1000



Conduit Clip Pins:

Item No.	Description	Jar	Case
PD157-100NR/CC38	3/8" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CC50	1/2" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CC75	3/4" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	600
PD157-100NR/CC100	1" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	600



Z Clip Pins:

Item No.	Description	Jar	Case
PD157-100NR/ZC25	1/4" thread Z clip w/.157" dia. shank, 1" nitro pin (red)	100	1000



▲ Conduit Clamp Pins:

Item No.	Description	Jar	Case
PD157-100NR/CP38	3/8" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CP50	1/2" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CP75	3/4" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	600
PD157-100NR/CP100	1" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	600



Pretied Wires with Nitro Ninja Pins:

Item No.	Description
Wxx+4/157-78HNCN	NJ clip w/.157" dia. shank, 7/8" shank lgth top hat nitro pin prettied 12 gauge wire of any length
Wxx+4/157-100HNCN	NJ clip w/.157" dia. shank, 1" shank lgth top hat nitro pin prettied 12 gauge wire of any length
Wxx+4/157-114HNCN	NJ clip w/.157" dia. shank, 1-1/4" shank lgth top hat nitro pin prettied 12 gauge wire of any length

▲ Available on Request



.27cal Powder Actuated Ceiling Tool BP-27C



Features and Benefits

- Slim tool. Fits in tight spaces.
- Automatic piston return.
- · Easy to remove retention collar for cleaning.
- For use in Acoustical, Electrical and Mechanical overhead applications.
- Compatible with Bluepoint Ninja Pole System.
- Uses standard .27 cal. 10 shot strip loads.

Technical Data

Dimensions: 13-3/4" x 6" x 1-1/2"

Weight: 3.0lb Fastener length: 1/2" - 1-1/4"

Load Type: .27cal. (6.8 x 11mm) 10 strip loads **Power Level:** Brown/2, Green/3, Yellow/4, Red/5

Item No.	Description
BP-27C	.27cal. Strip powder actuated fastening ceiling tool.



.27cal long strip loads





Item No.	Description
NJB1	Fastening tool bag w/ compartments & shoulder strap 16.5"x8.0"x9.0"

Fasteners & Assemblies

.300" Dia. Head (PD series), .157" & .145" Dia. Shank Drive Pins and Assemblies

8mm Head (DN series), .145" Dia. Shank Drive Pins and Assemblies





Light Weight Heavy Duty Multi-function Ceiling Poles

Item No.	Description	Adjustable length	Weight (Lbs)
PM48		4' to 8'	2.5
PM412		4' to 12'	3.4
PM612	Light Weight Heavy duty adjustable multifunction	6' to 12'	3.4
PM618	ceiling pole (MAGNESIUM) w/ rubber grip	6' to 18'	4.7
PM816		8' to 16'	4.2
PM824		8' to 24'	6.0







14 Bluepoint Fasteners www.bpfasteners.com

NINJA ACOUSTIC POLE ADAPTER SYSTEMS



Light Weight Heavy Duty Multi-function Ceiling Poles

PATENTED



Features and Benefits:

- Stackable
- Fits Viper™ (I, II, III) , Sniper, Nitroset™ and Ninja forced entry ceiling tool systems
- Fits Viper™ IV with an NPA4 adapter (See page 16)
- Most trigger operated PAT tools can be utilized with push actuated saddle (See page 16)
- Multiple attachment configurations on the same pole makes you and your crew more productive

Item No.	Description	Adjustable length	Weight (Lbs)
PM48		4' to 8'	2.5
PM412		4' to 12'	3.4
PM612	Light Weight Heavy duty adjustable multifunction	6' to 12'	3.4
PM618	ceiling pole (MAGNESIUM) w/ rubber grip	6' to 18'	4.7
PM816		8' to 16'	4.2
PM824		8' to 24'	6.0

* All adapters have 3/4"-16 SAE threads







Lag-Pro Magnesium Multi-function Poles

Item No.	Description	Adjustable length	Weight (Lbs)
PM48L		4' to 8'	2.5
PM412L		4' to 12'	3.4
PM612L	Light Weight Heavy duty adjustable multifunction	6' to 12'	3.4
PM618L	ceiling lag pole (MAGNESIUM) w/ rubber grip	6' to 18'	4.7
PM816L		8' to 16'	4.2
PM824L		8' to 24'	6.0





Lag-Pro Aluminum Poles

Features and Benefits:

- Used to install threaded rods, ceiling wires, jack chain, pretied wires etc. to a variety of ceiling structures
- · Best cost performance in the market
- This pole can be stacked with our Multi-function ceiling pole

Item No.	Description	Adjustable length	Weight (Lbs)
P48L		4' to 8'	3.5
P412L		4' to 12'	4.5
P612L	Lag-Pro Aluminum Adjustable Ceiling Pole	6' to 12'	4.5
P618L	Directly comparable with all competitors tools and adapters	6' to 18'	5.9
P816L	'	8' to 16'	7.4
P824L		8' to 24'	10.4









Acoustic Pole System Adapters



Adapter Kits



Item No.	Description	Include	Qty.
NPAK-1	Ninja Adapter Kit 1 includes the following: • Tie wire wedge anchor installer • Eye lag head • Pretied wire head • Hex drive adapter • Lock pin • Base attachment, 3/8" hex drive • Plastic case	NPDA1 NPA1 NPA2 NPA3 NPLP NPBA2 NPAK-1C	1 1 1 1 1 1



Item No.	Description	Include	Qty.
NPAK-2	Ninja Adapter Kit 2 includes the following: • Tie wire wedge anchor Installer • Eye lag head • Pretied wire head • Hex drive adapter • Connection adapter for Viper 4™ • Drill chuck adapter • Lock pin • Base attachment, 3/8" hex drive • Plastic case	NPDA1 NPA1 NPA2 NPA3 NPA4 NPA9 NPLP NPBA2 NPAK- 2C	2 2 2 2 1 1 4 3 1



Item No.	Description
NJB1	Fastening tool bag w/ compartments & shoulder strap 16.5"x8.0"x9.0"

* All adapters have 3/4"-16 SAE threads





Item No.	Description
NPA1	Eye lag head
NPA2	Pre-tied wire head adapter
NPA3	Hex drive adapter
NPA4	Connection adapter used with Viper 4 ™ PAT Tool
NPBA2	Base attachment, 3/8" hex drive
NPPCI	Purlin clip installation tool for PC25 and PCZ25 clips












Item No.	Description
NPDA1	Tie Wire Anchor Installer
NPLP	Lock Pin
NPA9	Drill Chuck Adapter
NPAFT	PAT Pole Saddle Head 2 Fits to: • Blue Point®BP-301C, BP-302A, BP-303A, BP-361 • Hilt® DX35, DX350, DX351,DX2 • Simpson® PT-27 • Ramset® Cobra, R25 • Powers® P3500, PA3500, P35s, P3600



Rivets

Features and Benefits

- ° Quick and easy installation from one side of the workpiece
- ° Available in Dome or Countersunk Head
- ° Colored Head match to Pantone, RAL or sample color upon request







Item No.	Description	Diameter	Rivet Length	Bag	Box	Case
AA42WBULK			0.275"	-	-	10000
AA42W1000	5052 Aluminum alloy Rivets with aluminum mandrels		0.275"	-	1000	20000
AA42W100			0.275"	100	1000	12000
AA44WBULK			0.4"	-	-	10000
AA44W1000		1/8"	0.4"	-	1000	20000
AA42B1000			0.275"	-	-	10000
AA42BBULK	5052 Aluminum alloy Rivets with aluminum mandrels		0.275"	-	1000	20000
AA44BBULK	and BLACK colored Head		0.4"	-	-	10000
AA44B1000			0.4"	-	1000	20000

TEE-Locator (Item# TL)





Fig. 2



Fig. 3

Riveters



HR-702 Hand Riveter (In 2 jaws)



HR-705 Hand Riveter (In 2 jaws) (up to 3/16" for all material)



HR-708 Hand Riveter (In 3 jaws) (up to 3/16" for all material)



PPK HD Punch Plier

▲ Available on Request

Instructions for use:

- TEE-LOCATOR is designed to be used with either 9/16" or 15/16" gridwork (Fig. 1.).
- ° Place the TEE-LOCATOR as shown in Fig. 2 or 3. The magnets will ensure that it sticks to the Gridwork. Be sure that the long leg is pointed to the wall to ensure it is at a 90 degree angle.
- The Cross-Tee will now be square to the wall and you can punch a hole through the Wall Angle and Cross-Tee before fastening it in place with a rivet.
- ° Remove TEE-LOCATOR from the Grid.

Bluepoint Fasteners www.bpfasteners.com 877-779-2583 17



Exclusive manufacturer of both PAT and Gas tools for insulation fasteners

Insulation FasteningTools:

BP-361N



BP-303N



GT-120N





▲ Available on Request



Powder Loads:


Item No.	Color	Power Level
27LS11L6	Black	6
27LS11L5	Red	5
27LS11L4	Yellow	4
27LS11L3	Green	3



.27 cal. Low Velocity Insulation Loads

IF60-125-158S





Insulation Washers:

	Item No.	Description	Insulation Thickness	Penetration Length	Bag	Case
	IF60-125-158S		1"-1 1/4"	1"	50	1000
l e	IF60-150-158S	.300" Dia. head, .145"157" step shank pin with 60mm dia. insulation washer.	1 1/2"	1"	50	
ᇤ	IF60-200-200S		2"	1"	50	900
CONCRETE	IF60-300-200S		3"	1"	50	600
8	IF60-400-200S		4"	1"	50	500
For	IF60-500-200S		5"	1"	25	300
	IF60-600-200S		6"	1"	25	300
	IF60-125-158K		1"-1 1/4"	1"	50	1000
١.	IF60-150-158K		1 1/2"	1"	50	
METAL	IF60-200-200K	.300" Dia. head, .157" knurled	2"	1"	50	900
	IF60-300-200K	shank pin with 60mm dia. insulation washer(For metal	3"	1"	50	600
	IF60-400-200K	studs, light metal frame etc.).	4"	1"	50	500
	IF60-500-200K	stade, light metal frame etc.).	5"	1"	25	400
	IF60-600-200K	1	6"	1"	25	300

PDIW36-38F10



* Metal Washer

PIWP112G



* Gray Plastic Washer

PIWP112W



* White Plastic Washer

Membrane Washer Pins:

Item No.	Description	Shank Dia.	Shank Length	Box	Case
PDIW36-38F10	000" " 445" "	.145"	1-1/2"	100	1000
PDIW36-51F10	.300" dia. head, .145" dia. shank drive pin w/ 36mm dia. metal round insulation washer	.145"	2"	50	500
PDIW36-63F10		.145"	2-1/2"	50	500
PDIW36-76F10		.145"	3"	50	500
PIWP112G	.300" dia. head, .145" dia. shank	.145"	1-1/2"	100	1000
PIWP112W	drive pin w/ 36mm dia. plastic	.145"	1-1/2"	100	1000
PIWP212W	round insulation washer	.145"	2-1/2"	100	1000



Pretied Ceiling Wire

- ° ICC-ES ESR-1530 certified pins
- Meets or exceeds wire standards ASTM A641-92
- ° All wires are tied with the hospital wrap
- Tie requirement to ensure maximum holding power as dictated by building code
- ° Wire gauge:8 thru 12 gauge
- ° Length:2', 4', 6', 8', 10', 12', 14', 16', 18', 20' available
- ° Custom lengths also available
- Multiple wire termination options(see below)
- Wire can be purchased by:
 - a) Container for maximum savings
 - b) Bundles of 100pcs capped and wrapped securely
 - c) Master bundles of 20-100pc bundles
 - d) Steel crates that are stackable

DiameterTensile RangeZinc Thickness0.105"75ksi max≥25g/m2

Straight Cut Wires:



Coiled Wire:

Technical Data - 12 gauge wire



Hospital Tied 8 & 9 Gauge Tied 12 Gauge Double Tied







Steel Crate Quantity

Bundles / Steel crate					
Wire length 4"	160 bdls				
Wire length 6"	140 bdls				
Wire length 8"	120 bdls				

Small bundle (Include 100pcs)







Wire Attachment Options: Custom tying to order.

Electric EZ Wire Tie Machine:

	Part No.	Description	Box	Case
	TWM1A	Electric EZ wire tie machine/ 110V (for 12 gauge wire)	1	1
	TWM3	Electric EZ wire tie machine/ 230V (for 8 and 9 gauge wire)	1	1



Wire Attachment Options

	Product	Part No.	Description	Box	Case
		EL200W	2" wood eye lag wood screw/ plain	100	1000
	9344124434444	EL300W	3" wood eye lag wood screw/ plain	100	1000
		EL300WB	3" wood eye lag wood screw/ plain/ Bulk	-	1000
		EL300WZ	3" wood eye lag wood screw/ white zinc	100	1000
		EL300WZB	3" wood eye lag wood screw/ white zinc/ Bulk	-	1000
<u>.</u>		EL400W	4" wood eye lag wood screw/ plain	100	1000
" [EL400WB	4" wood eye lag wood screw/ plain/ Bulk	-	1000
*	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	EL500W	5" wood eye lag wood screw/ plain	100	1000
		EL500WB	5" wood eye lag wood screw/ plain/ Bulk	-	1000
		EL75SD	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1000
		EL75SDB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	1000
	(0)	EL75SDZ	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1000
		EL75SDZB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	1000
*	5/16" BIG HOLE	EL75BSD	2" overall lgth, ~1/2" thread lgth, 3/4" from collar to self drill point, 5/16" Eye. Used for 16 to 22 gauge sheet metal.	100	1000
*		EL150SP	2-3/4" overall lgth, ~ 1-1/2" thread lgth. Sharp point. Used for 20 to 22 gauge metal decking and also in wood applications.	100	1000
<u>*</u>		EL200SD	3-1/4" overall lgth,~1-3/4" threaded lgth, 2" from collar to drill point. Used for 16 to 22 gauge sheet metal.	100	1000
		EL100DSD	2-1/4" overall lgth, 1" from collar to drill point, Deep Drilling eye lag screw, Blue Ruspert finish. Extra Wide tool tip enables it to be used for up to 1/4" thick structural steel.	100	1000
Ī	whith the transfer of the tran	EL14114	2-1/2" overall length, Concrete Eye Lag Screw, Blue Ruspert finish. High-low thread, thread lgth 1-1/4".	100	1000
Ī		TWA14114	1/4" x 1-1/4" Tie wire wedge anchor	100	1000
		TWA14200	1/4" x 2" Tie wire anchor	100	1000
		TWSP14114	1/4" x 1-1/4" Tie wire spike pin anchor	100	1000
		TWSP316114	3/16" x 1-1/4" Tie wire spike pin anchor	100	1000
		TWSA14114	1/4" x 1-1/4" Tie wire split drive anchor	100	1000
Ì		HBC25	Hammer-on beam clamp (1/8" - 1/4")	100	1000
		HBC50	Hammer-on beam clamp (5/16" -1/2")	100	1000
		PCZ25	Z-Purlin clip (1/8" -1/4")	100	1000
		PC25	C-Purlin clip (1/8" - 1/4")	100	1000
	1	AC90	14 gauge 90 degree angle clip Holes Ø5.5mm & Ø8mm	100	1000
		AB90	12 gauge heavy duty clip, 90 degree Holes Ø5.2mm & Ø10.5mm	100	1000
		AB45	12 gauge heavy duty clip, 45 degree Holes Ø5.2mm & Ø10.5mm	100	1000

- ▲ Available on Request * Bright Zinc Plating Available on Request



Toggle Bolts

Product	Item No.	Description	Weight Lbs./Case	Package
	TBA14414	1/4"-20 * 4-1/4" zinc plated tog- gle bolt, with 1-1/2" metal washer assembled	9.2	100 pcs/box, 6 boxes/carton
- (1)	TBSA14500	1/4"-20 * 5" zinc plated toggle bolt, with 1-1/2" metal washer & spring assembled	10.8	100 pcs/box, 6 boxes/carton

Wood Screws

Product	Item No.	Description	Вох	Lbs./ Box	Case
	EL200W	2" eye lag wood screw/ plain	100	1.50	1000
	EL300W	3" eye lag wood screw/ plain	100	2.20	1000
	EL300WB	3" eye lag wood screw/ plain/ Bulk	-	-	1000
Si is desirate in incinate institute in the lateral and the la	EL300WZ	3" eye lag wood screw/ white zinc	100	2.20	1000
C interestingues as	EL300WZB	3" eye lag wood screw/ white zinc/ Bulk	-	-	1000
	EL400W	4" eye lag wood screw/ plain	100	2.98	1000
	EL400WB	4" eye lag wood screw/ plain/ Bulk	-	-	1000
	EL500W	5" eye lag wood screw/ plain	100	3.81	1000
***************************************	EL500WB	5" eye lag wood screw/ plain/ Bulk	-	-	1000

Eye Lag Screws

*

*

*

*

	Product	Item No.	Description	Вох	Lbs./ Box	Case
	house	EL75SD	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1.92	1000
		EL75SDB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	-	1000
		EL75SDZ	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1.92	-
		EL75SDZB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	-	1000
	5/16" BIG HOLE	EL75BSD	2" overall lgth, ~1/2" thread lgth, 3/4" from collar to self drill point, 5/16" Eye. Used for 16 to 22 gauge sheet metal.	100	1.92	1000
. [EL150SP	2-3/4" overall lgth, ~ 1-1/2" thread lgth. Sharp point. Used for 20 to 22 gauge metal decking and also in wood applications.	100	2.74	1000
. [EL200SD	3-1/4" overall lgth,~1-3/4" threaded lgth, 2" from collar to drill point. Used for 16 to 22 gauge sheet metal.	100	3.04	1000
		EL100DSD	2-1/4" overall lgth, 1" from collar to drill point, Deep Drilling eye lag screw, Blue Ruspert finish. Extra Wide tool tip enables it to be used for up to 1/4" thick structural steel.	100	2.20	1000
	puliththiniti»	EL14114	2-1/2" overall lgth, Concrete Eye Lag Screw, Blue Ruspert finish. High-low thread, thread lgth 1-1/4".	100	2.30	1000

Super Screw for Concrete, Wood and Steel

Product	Item No.	Description	Вох	Case
	2520RC150SP	1/4-20 rod coupling, point to collar 1-1/2" lgth, heat treated screw, non-detachable hex coupling	100	1000
	3816RC150SP 3/8-16 rod coupling, point to collar 1-1/2" lgth, heat treated screw, non-detachable hex coupling		100	1000
	2520RC75SD 1/4-20 rod coupling, point to collar 3/4" lgth, self-drilling, heat treated screw, 16 to 22ga. Sheet metal, non-detachable hex coupling		100	1000
3816RC200SP 3/8-16 rod coupling with 2" sharp point screw,		100	1000	

▲ Available on Request ※ Bright Zinc Plating Available on Request



Attachments

	Item No.	Description	Вох	Lbs./Box
	BR10-75	Bridle Ring 10-24 X 3/4"	100	3.31
	BR10-200	Bridle Ring 10-24 X 2"	100	6.17
()	BR25-125	Bridle Ring 1/4"-20 X 1-1/4"	100	7.28
	BR25-200	Bridle Ring 1/4"-20 X 2"	100	10.36



	Part No.	Description	Вох	Lbs./ Case	Case
	PC25	C-Purlin clip 1/8"-1/4"	100	5.60	1000
	PCZ25	Z-Purlin clip 1/8"-1/4"	100	4.20	1000
	HBC25	Hammer-on beam clip 1/8"-1/4"	100	3.03	1000
	HBC50	Hammer-on beam clip 5/16"-1/2"	100	3.58	1000
	BC50	Beam clamp w/ two 1/4"-20 holes, for flanges up to 1/2" thick	100	11.64	1000
Ę	BCS50	Beam Clamp (Spring steel) w/ 1/4"-20 hole, for flanges up to 1/2" thick	100	5.19	1000
42	PC25-EC25	1/8"-1/4" Purlin Clip w/ 1/4"-20 Eye Coupling	100	7.72	1000
	PC25-EC38	1/8"-1/4" Purlin Clip w/ 3/8"-16 Eye Coupling	100	11.55	1000
	PCZ25-EC25	1/8"-1/4" Z-Purlin Clip w/ 1/4"-20 Eye Coupling	100	6.33	1000
TC.	HBC25-EC25	1/8"-1/4" Beam Clip w/ 1/4"-20 Eye Coupling	100	5.16	1000
	HBC50-EC25	5/16"-1/2" Beam Clip w/ 1/4"-20 Eye Coupling	100	5.71	1000
3	BW25	Bat-Wing clip for 1/4" rod and 12 gauge wire	100	2.84	1000

	Part No.	Description	Вох	Lbs./ Case	Case
	ZC25-P32	Z clip (w/ 1/4" threaded hole) w/ .145" shank dia., 1-1/4" shank lgth. pin	100	4.41	1000
T L	ZC25-P157-100	Z clip (w/ 1/4" threaded hole) w/ .157" shank dia., 1" shank lgth. pin	100	4.41	1000
	ZC25	Z clip (w/ 1/4" threaded hole)	100	3.68	1000
	EC25-AC90	Eye Coupling (1/4"-20) with 90 degree angle clip	100	5.00	1000
	EC25-ACP32	Eye Coupling (1/4"-20) with 90 degree angle clip pin (.145 shank dia., 1-1/4" shank lgth.)	100	5.46	1000
D ALS	RH3 RHITHIN	Dual thread rod hanger (1/4"-20 & 3/8"-16)	100	6.89	1000
	N100RH2	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ 1" lgth. shank NJ pin	100	8.20	1000
	N125SRH2	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ 1-1/4" shank lgth. NJ pin	100	8.33	1000
	PD157-100RH1	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ .157" shank, 1" lgth. pin	100	8.20	1000
	PD157-125RH1	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ .157" shank dia., 1-1/4" shank lgth. pin	100	8.32	1000
0	EC25	Eye coupling 1/4"-20	100	2.12	1000
	EC38	Eye coupling 3/8"-16	100	5.95	1000
3	AC90	14 gauge 90 degree angle clip	100	2.87	1000

▲ Available on Request

22 Bluepoint Fasteners www.bpfasteners.com 877-779-2583



Rod Hangers



Part No.	Description			
THI4	Rod hanger for 1/4" threaded rod, with thread impression	100		
THI6	Rod hanger for 3/8" threaded rod, with thread impression	100		

Flange Mounted Conduit Clips



Part No.	Description	Вох
HFC24CC6	3/8" MC/AC cable to 1/8" to 1/4" flange	100
HFC58CC6	3/8" MC/AC cable to 5/16" to 1/2" flange	100
HFC912CC6	3/8" MC/AC cable to 9/16" to 3/4" flange	100
HFC24CC812	1/2" or 3/4" hammer-on pipe clip for flanges 1/8"-1/4"	100
HFC58CC812	1/2" or 3/4" hammer-on pipe clip for flanges 5/16"-1/2"	100
HFC912CC812	1/2" or 3/4" hammer-on pipe clip for flanges 9/16"-3/4"	100
HFC24CC16	1" hammer-on Pipe clip for flange 1/8"-1/4"	100
HFC58CC16	1" hammer-on Pipe clip for flange 5/16"-1/2"	100
HFC912CC16	1" hammer-on Pipe clip for flange 9/16"-3/4"	100
HFC24CC20	1-1/4" hammer-on Pipe clip for flange 1/8"-1/4"	100
HFC58CC20	1-1/4" hammer-on Pipe clip for flange 5/16"-1/2"	100
HFC912CC20	1-1/4" hammer-on Pipe clip for flange 9/16"-3/4"	50
HFC24CC24	1-1/2" hammer-on Pipe clip for flange 1/8"-1/4"	50
HFC58CC24	1-1/2" hammer-on Pipe clip for flange 5/16"-1/2"	50
HFC912CC24	1-1/2" hammer-on Pipe clip for flange 9/16"-3/4"	50
HFC24CC32	2" hammer-on Pipe clip for flange 1/8"-1/4"	50
HFC58CC32	2" hammer-on Pipe clip for flange 5/16"-1/2"	50
HFC912CC32	2" hammer-on Pipe clip for flange 9/16"-3/4"	50



Part No.	Description	Вох
HFC24	Hammer-on flange clip, FT 1/8" to 1/4", bottom mount	100
HFC58	Hammer -on flange clip, FT 5/16" to 1/2", bottom mount	100
HFC96	Hammer -on flange clip, FT 9/16" to 3/8", bottom mount	100



Part No.	Description	Box
HFC24S	Hammer-on flange clip with 1/4"x3/8" stud for 1/8-1/4" flanges	100
HFC58S	Hammer-on flange clip with 1/4"x3/8" stud for 5/16-1/2" flanges	100
HFC96S	Hammer-on flange clip with 1/4"x3/8" stud for 9/16-3/8" flanges	100

▲ Available on Request















PH100

PH200

Available on Request



▲ Conduit Clip



▲ Conduit Clip w/ Pin



Pencil Rod



▲ Threaded Rod



Conduit clip, 1/2" to 3/4" Max load Vertical 100lbs. Horizontal 25lbs.

Part No.	Description	Вох	Case
CC50	1/2" Conduit clamp	100	1000
CC75	3/4" Conduit clamp	100	1000
CC100	1" Conduit clamp	100	1000
CC125	1-1/4" Conduit clamp	100	1000
CC150	1-1/2" Conduit clamp	100	1000
CC200	2" Conduit clamp	100	1000

For use with powder actuated tools Clip sizes from 1/2" to 1"

Part No.	Shank Lgth	Description	Box	Case
CC50-P25	1"	Conduit clip (1/2") w/ .300" head,	100	1000
CC50-P32	1-1/4"	.145" shank dia. pin	100	1000
CC75-P25	1"	Conduit clip (3/4") w/ .300" head,145" shank dia. pin	50	500
CC75-P32	1-1/4"		50	500
CC100-P25	1"	Conduit clip (1") w/ .300" head,	50	500
CC100-P32	1-1/4"	.145" shank dia. pin	50	500
CC25-P25	1"	Conduit clip (1/4") w/ .300" head, .145" shank dia. pin	100	1000
CC38-P25	1"	Conduit clip (3/8") w/ .300" head, .145" shank dia. pin	100	1000
CC75-DN25	1"	Conduit clip (3/4") w/ 8mm head, 3.7mm(.145") shank dia. pin	50	500

Diameter 1/4" Additional diameters and lengths available

Part No.	Description	Bundle	Pallet
5-4	Pencil rod 1/4" x 4'	100	TBD
PR25-6	Pencil rod 1/4" x 6'	100	TBD
PR25-8	Pencil rod 1/4" x 8'	100	TBD
PR25-10	Pencil rod 1/4" x 10"	100	TBD
PR25-12	Pencil rod 1/4" x 12'	100	TBD

All threaded rods, diameter 1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1" are available All lengths are available

Part No.	Description	Bundle	Pallet
TR25-4	Threaded rod/ All thread 1/4" x 4'	100	TBD
TR25-6	Threaded rod/ All thread 1/4" x 6'	100	TBD
TR25-8	Threaded rod/ All thread 1/4" x 8'	100	TBD
TR25-10	Threaded rod/ All thread 1/4" x 10'	100	TBD
TR25-12	Threaded rod/ All thread 1/4" x 12'	100	TBD

▲ Available on Request



Concrete Screws

- ° Available in 1/4" and 3/16" diameter
- ° No insert required
- ° Removable fastener
- ° Can be used in pressure treated lumber
- ° Available in either Philips head or hex head length up to 6"

Item No.	Description	Size	Box	Case
CSF316114		3/16" x 1-1/4"	100	1000
CSF316214		3/16" x 2-1/4"	100	1000
CSF316334]	3/16" x 3-3/4"	100	1000
CSF14114		1/4" x 1-1/4"	100	1000
CSF14134	Philips flat head concrete	1/4" x 1-3/4"	100	1000
CSF14214	screw	1/4" x 2-1/4"	100	1000
CSF14234		1/4" x 2-3/4"	100	1000
CSF14314]	1/4" x 3-1/4"	100	1000
CSF14334		1/4" x 3-3/4"	100	1000
CSF14400		1/4" x 4"	100	1000
CSH316114		3/16" x 1-1/4"	100	1000
CSH316214		3/16" x 2-1/4"	100	1000
CSH316334		3/16" x 3-3/4"	100	1000
CSH14114		1/4" x 1-1/4"	100	1000
CSH14134	5/16" Hex head	1/4" x 1-3/4"	100	1000
CSH14214	- 5/16 nextiead	1/4" x 2-1/4"	100	1000
CSH14234		1/4" x 2-3/4"	100	1000
CSH14314		1/4" x 3-1/4"	100	1000
CSH14334	1	1/4" x 3-3/4"	100	1000
CSH14400		1/4" x 4"	100	1000

Mechanical Anchors

Available in several designs for the best solution for your fastening requirements.

		Item No.	Description	Size	Вох	Case
ſ		SLA38178		3/8" x 1-7/8"	50	500
		SLA38300		3/8" x 3"	50	400
		SLA12214	Sleeve anchor hex nut	1/2" x 2-1/4"	25	250
	Transacari)	SLA12234		1/2" x 2-3/4"	25	250
		SLA12300		1/2" x 3"	25	200
		DIA1258200	Drop in anchor	1/2" x 5/8" x 2"	50	500
		DIA1258200T	Drop in anchor, w/ 1 tool/box	1/2" x 5/8" x 2"	50	500
		DIA38121916	Drop in anchor	3/8" x 1/2" x 1-9/16"	50	500
		DIA38121916T	Drop in anchor, w/ 1 tool/box	3/8" x 1/2" x 1-9/16"	50	500
		TWA14114	Tie wire wedge anchor	1/4" x 1-1/4"	100	1000
		TWA14200 🔺	The wife wedge afficion	1/4" x 2"	100	1000
		TWSA14114	Tie wire split anchor	1/4" x 1-1/4"	100	1000
		TWSP14114	Tie wire enike nin encher	1/4" x 1-1/4"	100	1000
.		TWSP316114	Tie wire spike pin anchor	3/16" x 1-1/4"		

▲ Available on Request



Mechanical Anchors

	Item No.	Description	Size	Box	Case
	WA38214		3/8" x 2-1/4"	50	500
	WA38234		3/8" x 2-3/4"	50	400
	WA38300		3/8" x 3"	50	400
	WA38312		3/8" x 3-1/2"	50	300
	WA38334		3/8" x 3-3/4"	50	300
	WA38500		3/8" x 5"	50	250
	WA38612		3/8" x 6-1/2"	50	250
	WA38800		3/8" x 8"	50	250
	WA12234		1/2" x 2-3/4"	25	200
	WA12334		1/2" x 3-3/4"	25	150
	WA12414		1/2" x 4-1/4	25	150
	WA12412		1/2" x 4-1/2"	25	150
	WA12512		1/2" x 5-1/2"	25	150
	WA12700		1/2" x 7"	25	150
	WA12812		1/2" x 8-1/2"	10	30
	WA121000		1/2" x 10"	10	30
	WA121200	Wedge anchor	1/2" x 12"	10	30
- A MAIN COMPANIES AND	WA58312		5/8" x 3-1/2"	10	100
	WA58412		5/8" x 4-1/2"	10	100
	WA58500		5/8" x 5"	10	100
	WA58600		5/8" x 6"	10	50
	WA58700		5/8" x 7"	10	30
	WA58812		5/8" x 8-1/2"	10	30
	WA581000		5/8" x 10"	10	30
	WA581200		5/8" x 12"	10	30
	WA34414		3/4" x 4-1/4"	10	60
	WA34434		3/4" x 4-3/4"	10	60
	WA34512		3/4" x 5-1/2'	10	50
	WA34614		3/4" x 6-1/4"	10	30
	WA34700		3/4" x 7"	10	30
	WA34812		3/4" x 8-1/2"	10	30
	WA341000		3/4" x 10"	10	30
	WA341200		3/4" x 12"	10	30
	NIZ1434		1/4" x 3/4"	100	1000
	NIZ31678		3/16" x 7/8"	100	1000
	NIZ14100		1/4" x 1"	100	1000
	NIZ14114	Zamac nail drive anchor	1/4" x 1-1/4"	100	1000
	NIZ14112		1/4" x 1-1/2"	100	1000
	NIZ14200		1/4" x 2"	100	1000
	NIZ14212		1/4" x 2-1/2"	100	1000
	NIZ14300		1/4" x 3"	100	1000
	NIP14100		1/4" x 1"	100	1000
	NIP14114		1/4" x 1-1/4"	100	1000
2	NIP14112	Plastic nail in anchor	1/4" x 1-1/2"	100	1000
	NIP14200		1/4" x 2"	100	1000
	NIP14212		1/4" x 2-1/2"	100	1000



Masonry Drill





ISO ANSI

Description

Shank: Cylindrical Shank, Reduced.

Precision: Squared tip for a better centering.

Long lasting: High grade carbide for a longer lasting

drill bit.

Finishing: New anti-rust finishing. **Speed:** Deeper grooves that improve the

evacuation of dust and making more efficient the hammer

drill.

Norms: ANSI - NF ISO 5468 - DIN 8039



Part No.	Туре	Description	Вох
DS183	STD	X´tra masonry drill bit zinc plated 1/8" x 3"	10
DS5166	STD	X'tra masonry drill bit zinc plated 5/16" x 6"	10
DS384	STD	X´tra masonry drill bit zinc plated 3/8" x 4"	10
DS386	STD	X´tra masonry drill bit zinc plated 3/8" x 6"	10
DS3812	STD	X´tra masonry drill bit zinc plated 3/8" x 12"	10
DS126	STD	X´tra masonry drill bit zinc plated 1/2" x 6"	10
DS1212	STD	X'tra masonry drill bit zinc plated 1/2" x 12"	10







SDS plus premium



- SDS+
- 2 Cutting edges
- 4 Lateral supports
- **Tungsten Carbide**
- Self-centering point
- Chiseling effect





Resists **Torsion**







Research and Development

More Material

Flex exerted in the lower section of a drill bit is the most likely destructive factor. The progressive core of the spiral adds material and increases the rigidity in this area which is subjected to extreme pressure

Anti-Blocking System

2 asymmetric cutting edges reduce the risk of blockage when in use on a particularly hard aggregate, or on rebar. The progressive core and the roundness of the flute allow optimal removal of dust and eliminates any risk of blocking due to dust accumulation

Heat Treatment

The hardness of concrete combined with the power of the drill unite to create compression. The heat treatment of the body allows the energy of the drill to be concentrated on the tungsten carbide tip (while absorbing shock waves).

Part No.	Description	Qty.
DX144	SDS plus premium 2 cutting edges 1/4" x 4"	Each
DX146	SDS plus premium 2 cutting edges 1/4" x 6"	Each
DX148	SDS plus premium 2 cutting edges 1/4" x 8"	Each
DX386	SDS plus premium 2 cutting edges 3/8" x 6"	Each
DX388	SDS plus premium 2 cutting edges 3/8" x 8"	Each
DX3812	SDS plus premium 2 cutting edges 3/8" x 12"	Each
DX128	SDS plus premium 2 cutting edges 1/2" x 8"	Each
DX1212	SDS plus premium 2 cutting edges 1/2" x 12"	Each
DX586	SDS plus premium 2 cutting edges 5/8" x 6"	Each
DX588	SDS plus premium 2 cutting edges 5/8" x 8"	Each
DX5812	SDS plus premium 2 cutting edges 5/8" x 12"	Each

Part No.	Description	Qty.
QX381116	3/8" X 1-1/16" QMAX	Each
QX121316	1/2" X 13/16" QMAX	Each
QX1211116	1/2" X 1-11/16" QMAX	Each
QX581316	5/8" X 1-3/16" QMAX	Each
QX582116	5/8" X 2-1/16" QMAX	Each

Part No.	Description	Qty.
AXSP2SDS	Spline to SDS Adapters	Each
AXSDS2SDSP	SDSMAX to SDS PLUS Adapter	Each






Heavy Duty - Dump Carts

- · Powder coated steel frame.
- · Heavy duty Swivel Casters.
- In-line HD bearings.
- · Seamless one-piece molded truck bodies.
- Easy to clean.
- Easily passes through commercial and residential doorways and onto elevators.
- · Dumping can be done by one person.
- Inset wheels protect walls, fixtures.

HDDC50





Item No.	Description
HDDC50	1/2 yard cart (complete kit/ no lid)
HDDC50-1	1/2 yard lid
HDDC50-2	1/2 yard rear steel wheel, a pair
HDDC50-3	1/2 yard front swivel caster wheel, a pair
HDDC50-4	1/2 yard powder coated steel frame
HDDC50-5	1/2 yard dump cart tub
HDDC50-6	1/2 yard Handle





1 Yard Dump Cart

Description	
1 yard cart (complete kit/ no lid)	
1 yard lid	
1 yard rear steel wheel, a pair	
1 yard front swivel caster wheel, a pair	
1 yard powder coated steel frame	
1 yard dump cart tub	
1 yard Handle	



Dump Carts Forklift Bracket

- Specially designed for forklifts to lift dump cart
- Fit for BLUEPOINT 1 yard dump cart
- Easy add-on bracket
- Capacity: 1250 lbs.

HDDC100-FB



30 Bluepoint Fasteners www.bpfasteners.com 877-779-2583



Features and Benefits of Service Carts:

- For transporting equipment, tools and heavy loads in any environment.
- · Tough enough for material handling and maintenance.
- Built-in storage bin in handle, perfect way to store small parts.
- Sturdy structure foam construction, won't rust, dent, chip or peel.
- · Rounded corners protect walls and furniture.
- · Disassembled for shipping, assembly instruction is included.

Vertical Handle Utility Carts



"500 lb Capacity"

SC4425 Cart

- Size: L 43.1" x W 24.6" x H 38.1"(Handle Height)
- Loading Capacity: 500Lbs.
- Caster Size: 5" x 1-1/4"; Caster Qty: 2 rigid + 2 swivel
- Cart Material: PP.; Color: Grey
- Net Weight: 44 Lbs.

Armor shown below is available

SC4425-EZA Armor (Cart not included)

- Fits SC4425 Cart
- · Easy and fast install. No tools required
- Also fits: Rubbermaid® FG452088BLA cart and Sur-Pro® 4426 Series carts and various other carts
- Can be locked with a padlock (Not included)
- Net Weight: 37 Lbs.; Size: L 36" x H 23" x W 2"



SC4425

SC4425-EZA







SC4425AR = SC4425 Cart + SC4425-EZA Armor

(Assembly Required)



"500 lb Capacity"

SC4217

- Size: L 41.3" x W 16.7" x H 34.6" (Handle Height).
- Loading Capacity: 500Lbs.
- Caster Size: 5" x 1-1/4"; Caster Qty: 2 rigid + 2 swivel.
- · Caster Material: TPR (Thermo-Plastic-Rubber).
- Cart Material: PP.; Color: Grey.
- Net Weight: 30.8 Lbs.

Flat Handle Utility Carts





"550 lb Capacity"

SCF3625

- Size: L 46.5" x W 25.5" x H 33.5"; Tray Size: 36" x 24.5"
- Loading Capacity: 550Lbs.
- Caster Size: 5" x 1"; Caster Qty: 2 rigid + 2 swivel
- Caster Material: TPR (Thermo-Plastic-Rubber)
- · Cart Material: PP; Color: Grey
- Net Weight: 45.0 Lbs.





"550 lb Capacity"

SCF3016

- Size: L 34.4" x W 17.1" x H 33.5"; Tray Size: 30" x 16"
- · Loading Capacity: 550Lbs.
- Caster Size: 5" x 1"; Caster Qty: 2 rigid + 2 swivel
- Caster Material: TPR (Thermo-Plastic-Rubber)
- · Cart Material: PP; Color: Grey
- Net Weight: 29.9 Lbs.



Hybrid PU Polymer Air Hose

- Temperature Range: -58°F to 248°F
- UV stabilized for long service life
- Tough and resistant to constant flexing
- · Extremely flexible making it easier to rewind
- Translucent orange, allowing easy visual inspection for lubrication or contamination In the field
- Up to 50% lighter than regular rubber hose



Features and Benefits:

- Extreme abrasion resistant
- Retains flexibility in subzero (-50 °F) temperature
- Resistant to oils and greases
- Resistant to chemicals; Non-marring outer coating
- Cover & Tube: Premium hybrid PU polymer
- Interlayer: Reinforced polyester



Item No.	Description
FA14100RC/3	1/4" x 100' air hose, W.P. 300psi
FA38100RC/3	3/8" x 100' air hose, W.P. 300psi

Jack Hammer Hose

 Nitrile construction, crimped sleeve crowfeet (Chicago Style)

Working pressure: 300psiBurst pressure: 1200psiSafety factor: 4:1



Features and Benefits:

- Nitrile tube and cover compound along with polyester braided reinforcement add up to a highly abrasion and oil resistant hose providing a long service life
- Temperature range: -40°F to +210°F

Item No.	Description
N3450JC20300	I.D. 3/4" x 50' Jack Hammer hose crimped sleeve crowfeet
N34100JC20300	I.D. 3/4" x 100' Jack Hammer hose crimped sleeve crowfeet

Industry Grade NBR Water Hose

Features and Benefits:

- Nitrile rubber water hose is of excellent cracking and abrasion resistance. Ideal for construction as well as farm and ranch watering applications
- 250psi W.P. with 4:1 safety factor
- Very durable and flexible, lays flat, zero memory



- Cold weather resistance up to -22°F, handles hot water up to 180°F, 30% lighter than regular rubber hose
- Kink resistant under pressure
- Easy coiling after use

Item No.	Description
WR5825	5/8" x 25' heavy-duty contractor water hose
WR5875	5/8" x 75' heavy-duty contractor water hose
WR58100	5/8" x 100' heavy-duty contractor water hose



NOTES

Bluepoint Fasteners www.bpfasteners.com 877-779-2583 33



Contact:

Chino,CA

14728 Yorba Court Chino, CA 91710, USA Phone: +1 877-779-2583 Fax: +1 866-672-9402 E-mail: info@bpfasteners.com

Dallas, TX

10203 Corkwood Road Dallas, TX 75238, USA Phone: +1 214-238-0441 E-mail: info@bpfasteners.com

Tijuana, Mexico

Paseo Aguila Azteca 20051
Plataforma 2 Nave 12
Fraccionamiento El Aguila
Tijuana, Baja California 22215, Mexico
Phone: +52 664-207-9999
E-mail: ventasmx@bpfasteners.com

Guadalajara, Mexico

Av. Moctezuma Num 246 Col. Cd del Sol Zapopan, Jal. Mexico 45050 Phone: +52 334-348-7196 E-mail: jc@bpfasteners.com

Our Brands:







