

25 YEARS OF DEDICATION TO CONSTRUCTION SPECIAL FASTENING SYSTEM IN USA



PROFESSIONAL GRADE HOSES

747/194:14

CONFIRM AND TESTED

HPPA14100CQ- AIR HOSE, 1/4" X 100, W.P. 300 PSI HPPA38100CQ - AIR HOSE, 3/8" X 100, W.P. 300 PSI



- **EXCEPTIONAL ABRASION RESISTANCE**
- NEVER KINK
- HIGH FLOW
- **BEND RESTRICTOR TO REDUCE WEAR & TEAR**
- UV, OZONE, CRACKING, CHEMICALS & OIL RESISTANT.



Premium Hybrid Pu Polymer Air Hose



- **300PSI WORKING PRESSURE**
- TEMPERATURE RANGE: -40°F TO 160°F
- **UV STABILIZED FOR LONG SERVICE LIFE**
- TOUGH AND RESISTANT TO CONSTANT FLEXING
- EXTREMELY FLEXIBLE MAKING IT EASIER TO REWIND
- TRANSLUCENT ORANGE, ALLOWING EASY VISUAL INSPECTION FOR LUBRICATION OR CONTAMINATION IN THE FIELD
- **EXTREME ABRASION RESISTANCE**
- RESISTANT TO OILS, GREASES, AND CHEMICALS
- **NON-MARRING OUTER COVER**
- REUSABLE BRASS FITTING FOR EASY FIELD REPAIRS



FA14100RC/3 - AIR HOSE, 1/4" X 100, W.P. 300 PSI FA38100RC/3 - AIR HOSE, 3/8" X 100, W.P. 300 PSI

JACK HAMMER HOSE



- MATERIAL: NITRILE
- CRIMPED SLEEVE CROWFEET (CHICAGO STYLE)
- **300PSI WORKING PRESSURE, 1200PSI BURST PRESSURE**
- SALLTY FACTOR: 4:1
- TEMPERATURE RANGE: -40°F TO +210°F

HJC3450 - I.D. 3/4" X 50' JACK HAMMER HOSE W/ CRIMPED SLEEVE CROWFEET HJC34100 - I.D. 3/4" X 100' JACK HAMMER HOSE W/ CRIMPED SLEEVE CROWFEET